

Module LLE 24mm 650lm HV ADV5

Modules LLE advanced



LLE 24x70mm 160lm HV ADV5



LLE 24x140mm 325lm HV ADV5



LLE 24x280mm 650lm HV ADV5

Product description

- _ Ideal for linear and panel lights
- _ 2 terminals for serial wiring
- _ Perfectly uniform light, even if several LED modules are used together in a line
- _ Push terminals for quick and simple wiring of LED module to LED module
- _ Option backside terminal
- _ Broad portfolio from extruded lenses and covers available
- _ HE ... High Efficiency, NM ... Nominal Mode, HO ... High Output
- _ Min. order quantity LLE 24x70mm QTY4: 36 pcs. The LLE 24x70mm QTY4 module contains 4 single 24x70mm modules which have to be separated
- _ Long lifetime up to 72,000 hours
- _ 5 years guarantee (conditions at <https://www.tridonic.com/manufacturer-guarantee-conditions>)

Optical properties

- _ Colour temperatures 2,700, 3,000, 3,500, 4,000, 5,000 and 6,500 K
- _ Useful luminous flux 1,428 lm at Irated and tp = 25 °C
- _ Efficacy of the LED module 200 lm/W at Irated and tp = 25 °C
- _ High colour rendering index CRI > 80
- _ High colour consistency (MacAdam 3) ①
- _ Small luminous flux tolerances

Mechanical properties

- _ Module dimension 24 x 70 mm, 24 x 140 mm, 24 x 280 mm and 24 x 560 mm (ZHAGA compliant)
- _ Simple installation via clips or screws



System solution

- _ Combine Tridonic's LED modules and dimmable drivers to achieve an outstanding system efficacy (configuration possible via <https://setbuilder.tridonic.com/>)

① Integral measurement over the complete module.


Website

<http://www.tridonic.com/89603180>




Module LLE 24mm 650lm HV ADV5


Modules LLE advanced




LLE 24x70mm 160lm HV ADV5



LLE 24x140mm 325lm HV ADV5



LLE 24x280mm 650lm HV ADV5



LLE 24x560mm 1300lm HV ADV5

Ordering data

Type	Article number	Colour temperature	Packaging, carton	Weight per pc.
Frontside terminal				
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	3,000 K	108 pc(s).	0.022 kg
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	4,000 K	108 pc(s).	0.022 kg
LLE 24x140mm 325lm 827 HV ADV5	89603182	2,700 K	108 pc(s).	0.011 kg
LLE 24x140mm 325lm 830 HV ADV5	89603183	3,000 K	108 pc(s).	0.010 kg
LLE 24x140mm 325lm 835 HV ADV5	28003388	3,500 K	108 pc(s).	0.010 kg
LLE 24x140mm 325lm 840 HV ADV5	89603184	4,000 K	108 pc(s).	0.010 kg
LLE 24x140mm 325lm 865 HV ADV5	89603186	6,500 K	108 pc(s).	0.011 kg
LLE 24x280mm 650lm 827 HV ADV5	89603187	2,700 K	108 pc(s).	0.021 kg
LLE 24x280mm 650lm 830 HV ADV5	89603188	3,000 K	108 pc(s).	0.021 kg
LLE 24x280mm 650lm 835 HV ADV5	28003395	3,500 K	108 pc(s).	0.021 kg
LLE 24x280mm 650lm 840 HV ADV5	89603189	4,000 K	108 pc(s).	0.021 kg
LLE 24x280mm 650lm 850 HV ADV5	89603190	5,000 K	108 pc(s).	0.021 kg
LLE 24x280mm 650lm 865 HV ADV5	89603191	6,500 K	108 pc(s).	0.021 kg
LLE 24x560mm 1300lm 827 HV ADV5	89603192	2,700 K	108 pc(s).	0.041 kg
LLE 24x560mm 1300lm 830 HV ADV5	89603193	3,000 K	108 pc(s).	0.041 kg
LLE 24x560mm 1300lm 835 HV ADV5	28003397	3,500 K	108 pc(s).	0.041 kg
LLE 24x560mm 1300lm 840 HV ADV5	89603194	4,000 K	108 pc(s).	0.041 kg
LLE 24x560mm 1300lm 850 HV ADV5	89603195	5,000 K	108 pc(s).	0.041 kg
LLE 24x560mm 1300lm 865 HV ADV5	89603196	6,500 K	108 pc(s).	0.041 kg
Backside terminal				
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	4,000 K	120 pc(s).	0.041 kg
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	6,500 K	120 pc(s).	0.041 kg

Technical data

Beam characteristic	120°
Ambient temperature t_a	-40 ... +65 °C
t_p rated	50 °C
t_c	85 °C
I_{rated}	300 mA
I_{max}	540 mA
Max. permissible LF current ripple	595 mA
Max. permissible peak current	900 mA / max. 10 ms
Max. working voltage for insulation [®]	440 V
Insulation test voltage	1.88 kV
CTI of the printed circuit board	≥ 600
ESD classification	Severity level 4
Risk group (IEC 62471)	RG0
Classification acc. to IEC 62031	Built-in
Type of protection	IPO0
Lumen maintenance L70B50	72,000 h
Guarantee (conditions at www.tridonic.com)	5 Year(s)

Approval marks**Standards**

IEC 62031, IEC 62471, IEC 61000-4-2, IEC 62778, IEC 61547, UL 8750

Specific technical data

Type	Article number	Photometric code	Useful luminous flux at tp = 25 °C [®]	Expected luminous flux at tp rated [®]	Typ. forward current	Min. forward voltage at tp rated [®]	Max. forward voltage at tp = 25 °C [®]	Power consumption Pon at tp = 25 °C [®]	Efficacy of the module at tp = 25 °C	Expected efficacy of the module at tp rated	Colour rendering index CRI
Operating mode HE at 200 mA											
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	830/359	-	100 lm	200 mA	2.6 V	2.8 V	-	-	186 lm/W	>>80
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	840/359	-	107 lm	200 mA	2.6 V	2.8 V	-	-	196 lm/W	>>80
LLE 24x140mm 325lm 827 HV ADV5	89603182	827/359	-	200 lm	200 mA	5.2 V	5.6 V	-	-	184 lm/W	>>80
LLE 24x140mm 325lm 830 HV ADV5	89603183	830/359	-	205 lm	200 mA	5.2 V	5.6 V	-	-	187 lm/W	>>80
LLE 24x140mm 325lm 835 HV ADV5	28003388	835/359	-	210 lm	200 mA	5.2 V	5.6 V	-	-	194 lm/W	>>80
LLE 24x140mm 325lm 840 HV ADV5	89603184	840/359	-	212 lm	200 mA	5.2 V	5.6 V	-	-	196 lm/W	>>80
LLE 24x140mm 325lm 865 HV ADV5	89603186	865/359	-	214 lm	200 mA	5.2 V	5.6 V	-	-	197 lm/W	>>80
LLE 24x280mm 650lm 827 HV ADV5	89603187	827/359	-	391 lm	200 mA	10.3 V	11.2 V	-	-	183 lm/W	>>80
LLE 24x280mm 650lm 830 HV ADV5	89603188	830/359	-	404 lm	200 mA	10.3 V	11.2 V	-	-	189 lm/W	>>80
LLE 24x280mm 650lm 835 HV ADV5	28003395	835/359	-	419 lm	200 mA	10.3 V	11.2 V	-	-	193 lm/W	>>80
LLE 24x280mm 650lm 840 HV ADV5	89603189	840/359	-	423 lm	200 mA	10.3 V	11.2 V	-	-	196 lm/W	>>80
LLE 24x280mm 650lm 850 HV ADV5	89603190	850/359	-	423 lm	200 mA	10.3 V	11.2 V	-	-	196 lm/W	>>80
LLE 24x280mm 650lm 865 HV ADV5	89603191	865/359	-	428 lm	200 mA	10.3 V	11.2 V	-	-	195 lm/W	>>80
LLE 24x560mm 1300lm 827 HV ADV5	89603192	827/359	-	779 lm	200 mA	20.7 V	22.4 V	-	-	180 lm/W	>>80
LLE 24x560mm 1300lm 830 HV ADV5	89603193	830/359	-	806 lm	200 mA	20.7 V	22.4 V	-	-	187 lm/W	>>80
LLE 24x560mm 1300lm 835 HV ADV5	28003397	835/359	-	834 lm	200 mA	20.7 V	22.4 V	-	-	192 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5	89603194	840/359	-	845 lm	200 mA	20.7 V	22.4 V	-	-	195 lm/W	>>80
LLE 24x560mm 1300lm 850 HV ADV5	89603195	850/359	-	850 lm	200 mA	20.7 V	22.4 V	-	-	196 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5	89603196	865/359	-	844 lm	200 mA	20.7 V	22.4 V	-	-	195 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	840/359	-	845 lm	200 mA	20.7 V	22.4 V	-	-	193 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	865/359	-	844 lm	200 mA	20.7 V	22.4 V	-	-	194 lm/W	>>80
Operating mode HE at 250 mA											
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	830/359	-	124 lm	250 mA	2.6 V	2.8 V	-	-	181 lm/W	>>80
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	840/359	-	132 lm	250 mA	2.6 V	2.8 V	-	-	191 lm/W	>>80
LLE 24x140mm 325lm 827 HV ADV5	89603182	827/359	-	240 lm	250 mA	5.2 V	5.7 V	-	-	177 lm/W	>>80
LLE 24x140mm 325lm 830 HV ADV5	89603183	830/359	-	249 lm	250 mA	5.2 V	5.7 V	-	-	182 lm/W	>>80
LLE 24x140mm 325lm 835 HV ADV5	28003388	835/359	-	260 lm	250 mA	5.2 V	5.7 V	-	-	189 lm/W	>>80
LLE 24x140mm 325lm 840 HV ADV5	89603184	840/359	-	260 lm	250 mA	5.2 V	5.7 V	-	-	191 lm/W	>>80
LLE 24x140mm 325lm 865 HV ADV5	89603186	865/359	-	263 lm	250 mA	5.2 V	5.7 V	-	-	192 lm/W	>>80
LLE 24x280mm 650lm 827 HV ADV5	89603187	827/359	-	480 lm	250 mA	10.4 V	11.3 V	-	-	170 lm/W	>>80
LLE 24x280mm 650lm 830 HV ADV5	89603188	830/359	-	502 lm	250 mA	10.4 V	11.3 V	-	-	184 lm/W	>>80
LLE 24x280mm 650lm 835 HV ADV5	28003395	835/359	-	513 lm	250 mA	10.4 V	11.3 V	-	-	188 lm/W	>>80
LLE 24x280mm 650lm 840 HV ADV5	89603189	840/359	-	520 lm	250 mA	10.4 V	11.3 V	-	-	191 lm/W	>>80
LLE 24x280mm 650lm 850 HV ADV5	89603190	850/359	-	513 lm	250 mA	10.4 V	11.3 V	-	-	188 lm/W	>>80
LLE 24x280mm 650lm 865 HV ADV5	89603191	865/359	-	520 lm	250 mA	10.4 V	11.3 V	-	-	190 lm/W	>>80
LLE 24x560mm 1300lm 827 HV ADV5	89603192	827/359	-	960 lm	250 mA	20.9 V	22.6 V	-	-	175 lm/W	>>80
LLE 24x560mm 1300lm 830 HV ADV5	89603193	830/359	-	1,001 lm	250 mA	20.9 V	22.6 V	-	-	182 lm/W	>>80
LLE 24x560mm 1300lm 835 HV ADV5	28003397	835/359	-	1,023 lm	250 mA	20.9 V	22.6 V	-	-	187 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5	89603194	840/359	-	1,034 lm	250 mA	20.9 V	22.6 V	-	-	190 lm/W	>>80
LLE 24x560mm 1300lm 850 HV ADV5	89603195	850/359	-	1,026 lm	250 mA	20.9 V	22.6 V	-	-	188 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5	89603196	865/359	-	1,032 lm	250 mA	20.9 V	22.6 V	-	-	190 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	840/359	-	1,034 lm	250 mA	20.9 V	22.6 V	-	-	188 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	865/359	-	1,032 lm	250 mA	20.9 V	22.6 V	-	-	189 lm/W	>>80
Operating mode HE at 275 mA											
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	830/359	-	134 lm	275 mA	2.6 V	2.8 V	-	-	176 lm/W	>>80
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	840/359	-	141 lm	275 mA	2.6 V	2.8 V	-	-	187 lm/W	>>80
LLE 24x140mm 325lm 827 HV ADV5	89603182	827/359	-	260 lm	275 mA	5.3 V	5.7 V	-	-	173 lm/W	>>80
LLE 24x140mm 325lm 830 HV ADV5	89603183	830/359	-	269 lm	275 mA	5.3 V	5.7 V	-	-	178 lm/W	>>80
LLE 24x140mm 325lm 835 HV ADV5	28003388	835/359	-	280 lm	275 mA	5.3 V	5.7 V	-	-	185 lm/W	>>80
LLE 24x140mm 325lm 840 HV ADV5	89603184	840/359	-	279 lm	275 mA	5.3 V	5.7 V	-	-	188 lm/W	>>80
LLE 24x140mm 325lm 865 HV ADV5	89603186	865/359	-	282 lm	275 mA	5.3 V	5.7 V	-	-	188 lm/W	>>80
LLE 24x280mm 650lm 827 HV ADV5	89603187	827/359	-	520 lm	275 mA	10.5 V	11.4 V	-	-	174 lm/W	>>80
LLE 24x280mm 650lm 830 HV ADV5	89603188	830/359	-	541 lm	275 mA	10.5 V	11.4 V	-	-	180 lm/W	>>80
LLE 24x280mm 650lm 835 HV ADV5	28003395	835/359	-	558 lm	275 mA	10.5 V	11.4 V	-	-	184 lm/W	>>80
LLE 24x280mm 650lm 840 HV ADV5	89603189	840/359	-	559 lm	275 mA	10.5 V	11.4 V	-	-	187 lm/W	>>80
LLE 24x280mm 650lm 850 HV ADV5	89603190	850/359	-	551 lm	275 mA	10.5 V	11.4 V	-	-	184 lm/W	>>80
LLE 24x280mm 650lm 865 HV ADV5	89603191	865/359	-	559 lm	275 mA	10.5 V	11.4 V	-	-	186 lm/W	>>80
LLE 24x560mm 1300lm 827 HV ADV5	89603192	827/359	-	1,038 lm	275 mA	21.0 V	22.7 V	-	-	171 lm/W	>>80
LLE 24x560mm 1300lm 830 HV ADV5	89603193	830/359	-	1,078 lm	275 mA	21.0 V	22.7 V	-	-	177 lm/W	>>80
LLE 24x560mm 1300lm 835 HV ADV5	28003397	835/359	-	1,112 lm	275 mA	21.0 V	22.7 V	-	-	183 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5	89603194	840/359	-	1,110 lm	275 mA	21.0 V	22.7 V	-	-	186 lm/W	>>80
LLE 24x560mm 1300lm 850 HV ADV5	89603195	850/359	-	1,121 lm	275 mA	21.0 V	22.7 V	-	-	184 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5	89603196	865/359	-	1,114 lm	275 mA	21.0 V	22.7 V	-	-	186 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	840/359	-	1,110 lm	275 mA	21.0 V	22.7 V	-	-	184 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	865/359	-	1,114 lm	275 mA	21.0 V	22.7 V	-	-	185 lm/W	>>80
Operating mode NM at 300 mA											
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	830/359	148 lm	143 lm	300 mA	2.6 V	2.9 V	0.83 W	178 lm/W	175 lm/W	>>80

Type	Article number	Photometric code	Useful luminous flux at $t_p = 25^\circ\text{C}$	Expected luminous flux at t_p rated	Typ. forward current	Min. forward voltage at t_p rated	Max. forward voltage at $t_p = 25^\circ\text{C}$	Power consumption P_{on} at $t_p = 25^\circ\text{C}$	Efficacy of the module at $t_p = 25^\circ\text{C}$	Expected efficacy of the module at t_p rated	Colour rendering index CRI
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	840/359	156 lm	151 lm	300 mA	2.6 V	2.9 V	0.83 W	188 lm/W	184 lm/W	>>80
LLE 24x140mm 325lm 827 HV ADV5	89603182	827/359	295 lm	285 lm	300 mA	5.3 V	5.7 V	1.70 W	176 lm/W	173 lm/W	>>80
LLE 24x140mm 325lm 830 HV ADV5	89603183	830/359	298 lm	293 lm	300 mA	5.3 V	5.7 V	1.66 W	180 lm/W	177 lm/W	>>80
LLE 24x140mm 325lm 835 HV ADV5	28003388	835/359	310 lm	300 lm	300 mA	5.3 V	5.7 V	1.66 W	187 lm/W	183 lm/W	>>80
LLE 24x140mm 325lm 840 HV ADV5	89603184	840/359	313 lm	303 lm	300 mA	5.3 V	5.7 V	1.66 W	189 lm/W	185 lm/W	>>80
LLE 24x140mm 325lm 865 HV ADV5	89603186	865/359	316 lm	306 lm	300 mA	5.3 V	5.7 V	1.66 W	190 lm/W	186 lm/W	>>80
LLE 24x280mm 650lm 827 HV ADV5	89603187	827/359	579 lm	564 lm	300 mA	10.5 V	11.4 V	3.30 W	175 lm/W	172 lm/W	>>80
LLE 24x280mm 650lm 830 HV ADV5	89603188	830/359	599 lm	584 lm	300 mA	10.5 V	11.4 V	3.30 W	182 lm/W	179 lm/W	>>80
LLE 24x280mm 650lm 835 HV ADV5	28003395	835/359	618 lm	603 lm	300 mA	10.5 V	11.4 V	3.33 W	186 lm/W	182 lm/W	>>80
LLE 24x280mm 650lm 840 HV ADV5	89603189	840/359	627 lm	612 lm	300 mA	10.5 V	11.4 V	3.33 W	188 lm/W	184 lm/W	>>80
LLE 24x280mm 650lm 850 HV ADV5	89603190	850/359	627 lm	613 lm	300 mA	10.5 V	11.4 V	3.33 W	188 lm/W	185 lm/W	>>80
LLE 24x280mm 650lm 865 HV ADV5	89603191	865/359	627 lm	612 lm	300 mA	10.5 V	11.4 V	3.33 W	188 lm/W	184 lm/W	>>80
LLE 24x560mm 1300lm 827 HV ADV5	89603192	827/359	1,146 lm	1,117 lm	300 mA	21.1 V	22.8 V	6.66 W	172 lm/W	169 lm/W	>>80
LLE 24x560mm 1300lm 830 HV ADV5	89603193	830/359	1,195 lm	1,166 lm	300 mA	21.1 V	22.8 V	6.66 W	179 lm/W	177 lm/W	>>80
LLE 24x560mm 1300lm 835 HV ADV5	28003397	835/359	1,231 lm	1,201 lm	300 mA	21.1 V	22.8 V	6.66 W	185 lm/W	181 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5	89603194	840/359	1,234 lm	1,205 lm	300 mA	21.1 V	22.8 V	6.66 W	187 lm/W	183 lm/W	>>80
LLE 24x560mm 1300lm 850 HV ADV5	89603195	850/359	1,254 lm	1,226 lm	300 mA	21.1 V	22.8 V	6.66 W	188 lm/W	185 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5	89603196	865/359	1,248 lm	1,210 lm	300 mA	21.1 V	22.8 V	6.66 W	188 lm/W	184 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	840/359	1,234 lm	1,205 lm	300 mA	21.1 V	22.8 V	6.66 W	185 lm/W	181 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	865/359	1,248 lm	1,210 lm	300 mA	21.1 V	22.8 V	6.66 W	187 lm/W	184 lm/W	>>80
Operating mode HO at 350 mA											
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	830/359	-	167 lm	350 mA	2.7 V	2.9 V	-	-	172 lm/W	>>80
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	840/359	-	176 lm	350 mA	2.7 V	2.9 V	-	-	181 lm/W	>>80
LLE 24x140mm 325lm 827 HV ADV5	89603182	827/359	-	325 lm	350 mA	5.3 V	5.8 V	-	-	168 lm/W	>>80
LLE 24x140mm 325lm 830 HV ADV5	89603183	830/359	-	342 lm	350 mA	5.3 V	5.8 V	-	-	173 lm/W	>>80
LLE 24x140mm 325lm 835 HV ADV5	28003388	835/359	-	350 lm	350 mA	5.3 V	5.8 V	-	-	180 lm/W	>>80
LLE 24x140mm 325lm 840 HV ADV5	89603184	840/359	-	347 lm	350 mA	5.3 V	5.8 V	-	-	182 lm/W	>>80
LLE 24x140mm 325lm 865 HV ADV5	89603186	865/359	-	350 lm	350 mA	5.3 V	5.8 V	-	-	183 lm/W	>>80
LLE 24x280mm 650lm 827 HV ADV5	89603187	827/359	-	653 lm	350 mA	10.6 V	11.5 V	-	-	169 lm/W	>>80
LLE 24x280mm 650lm 830 HV ADV5	89603188	830/359	-	672 lm	350 mA	10.6 V	11.5 V	-	-	175 lm/W	>>80
LLE 24x280mm 650lm 835 HV ADV5	28003395	835/359	-	698 lm	350 mA	10.6 V	11.5 V	-	-	179 lm/W	>>80
LLE 24x280mm 650lm 840 HV ADV5	89603189	840/359	-	705 lm	350 mA	10.6 V	11.5 V	-	-	181 lm/W	>>80
LLE 24x280mm 650lm 850 HV ADV5	89603190	850/359	-	698 lm	350 mA	10.6 V	11.5 V	-	-	179 lm/W	>>80
LLE 24x280mm 650lm 865 HV ADV5	89603191	865/359	-	705 lm	350 mA	10.6 V	11.5 V	-	-	181 lm/W	>>80
LLE 24x560mm 1300lm 827 HV ADV5	89603192	827/359	-	1,293 lm	350 mA	21.3 V	23.0 V	-	-	166 lm/W	>>80
LLE 24x560mm 1300lm 830 HV ADV5	89603193	830/359	-	1,341 lm	350 mA	21.3 V	23.0 V	-	-	173 lm/W	>>80
LLE 24x560mm 1300lm 835 HV ADV5	28003397	835/359	-	1,390 lm	350 mA	21.3 V	23.0 V	-	-	178 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5	89603194	840/359	-	1,401 lm	350 mA	21.3 V	23.0 V	-	-	180 lm/W	>>80
LLE 24x560mm 1300lm 850 HV ADV5	89603195	850/359	-	1,397 lm	350 mA	21.3 V	23.0 V	-	-	179 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5	89603196	865/359	-	1,399 lm	350 mA	21.3 V	23.0 V	-	-	181 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	840/359	-	1,401 lm	350 mA	21.3 V	23.0 V	-	-	179 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	865/359	-	1,399 lm	350 mA	21.3 V	23.0 V	-	-	180 lm/W	>>80
Operating mode HO at 400 mA											
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	830/359	-	186 lm	400 mA	2.7 V	2.9 V	-	-	172 lm/W	>>80
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	840/359	-	200 lm	400 mA	2.7 V	2.9 V	-	-	180 lm/W	>>80
LLE 24x140mm 325lm 827 HV ADV5	89603182	827/359	-	375 lm	400 mA	5.4 V	5.8 V	-	-	168 lm/W	>>80
LLE 24x140mm 325lm 830 HV ADV5	89603183	830/359	-	391 lm	400 mA	5.4 V	5.8 V	-	-	173 lm/W	>>80
LLE 24x140mm 325lm 835 HV ADV5	28003388	835/359	-	400 lm	400 mA	5.4 V	5.8 V	-	-	179 lm/W	>>80
LLE 24x140mm 325lm 840 HV ADV5	89603184	840/359	-	400 lm	400 mA	5.4 V	5.8 V	-	-	181 lm/W	>>80
LLE 24x140mm 325lm 865 HV ADV5	89603186	865/359	-	404 lm	400 mA	5.4 V	5.8 V	-	-	182 lm/W	>>80
LLE 24x280mm 650lm 827 HV ADV5	89603187	827/359	-	752 lm	400 mA	10.7 V	11.6 V	-	-	169 lm/W	>>80
LLE 24x280mm 650lm 830 HV ADV5	89603188	830/359	-	769 lm	400 mA	10.7 V	11.6 V	-	-	175 lm/W	>>80
LLE 24x280mm 650lm 835 HV ADV5	28003395	835/359	-	802 lm	400 mA	10.7 V	11.6 V	-	-	178 lm/W	>>80
LLE 24x280mm 650lm 840 HV ADV5	89603189	840/359	-	812 lm	400 mA	10.7 V	11.6 V	-	-	181 lm/W	>>80
LLE 24x280mm 650lm 850 HV ADV5	89603190	850/359	-	798 lm	400 mA	10.7 V	11.6 V	-	-	178 lm/W	>>80
LLE 24x280mm 650lm 865 HV ADV5	89603191	865/359	-	812 lm	400 mA	10.7 V	11.6 V	-	-	180 lm/W	>>80
LLE 24x560mm 1300lm 827 HV ADV5	89603192	827/359	-	1,489 lm	400 mA	21.5 V	23.2 V	-	-	166 lm/W	>>80
LLE 24x560mm 1300lm 830 HV ADV5	89603193	830/359	-	1,545 lm	400 mA	21.5 V	23.2 V	-	-	173 lm/W	>>80
LLE 24x560mm 1300lm 835 HV ADV5	28003397	835/359	-	1,598 lm	400 mA	21.5 V	23.2 V	-	-	177 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5	89603194	840/359	-	1,598 lm	400 mA	21.5 V	23.2 V	-	-	179 lm/W	>>80
LLE 24x560mm 1300lm 850 HV ADV5	89603195	850/359	-	1,596 lm	400 mA	21.5 V	23.2 V	-	-	178 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5	89603196	865/359	-	1,603 lm	400 mA	21.5 V	23.2 V	-	-	180 lm/W	>>80
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	840/359	-	1,598 lm	400 mA	21.5 V	23.2 V	-	-	178 lm/W	>>80
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	865/359	-	1,603 lm	400 mA	21.5 V	23.2 V	-	-	179 lm/W	>>80
Operating mode HO at 500 mA											
LLE 24x70mm 160lm 830 HV ADV5 QTY4	89603180	830/359	-	229 lm	500 mA	2.7 V	2.9 V	-	-	164 lm/W	>>80
LLE 24x70mm 160lm 840 HV ADV5 QTY4	89603181	840/359	-	249 lm	500 mA	2.7 V	2.9 V	-	-	172 lm/W	>>80
LLE 24x140mm 325lm 827 HV ADV5	89603182	827/359	-	460 lm	500 mA	5.5 V	5.9 V	-	-	162 lm/W	>>80
LLE 24x140mm 325lm 830 HV ADV5	89603183	830/359	-	469 lm	500 mA	5.5 V	5.9 V	-	-	165 lm/W	>>80

Type	Article number	Photometric code	Useful luminous flux at $t_p = 25\text{ }^\circ\text{C}$ ^②	Expected luminous flux at t_p rated	Typ. forward current	Min. forward voltage at t_p rated ^③	Max. forward voltage at $t_p = 25\text{ }^\circ\text{C}$ ^④	Power consumption P_{on} at $t_p = 25\text{ }^\circ\text{C}$ ^⑤	Efficacy of the module at $t_p = 25\text{ }^\circ\text{C}$	Expected efficacy of the module at t_p rated	Colour rendering index CRI
LLE 24x140mm 325lm 835 HV ADV5	28003388	835/359	-	490 lm	500 mA	5.5 V	5.9 V	-	-	171 lm/W	> >80
LLE 24x140mm 325lm 840 HV ADV5	89603184	840/359	-	486 lm	500 mA	5.5 V	5.9 V	-	-	173 lm/W	> >80
LLE 24x140mm 325lm 865 HV ADV5	89603186	865/359	-	496 lm	500 mA	5.5 V	5.9 V	-	-	175 lm/W	> >80
LLE 24x280mm 650lm 827 HV ADV5	89603187	827/359	-	911 lm	500 mA	10.9 V	11.8 V	-	-	161 lm/W	> >80
LLE 24x280mm 650lm 830 HV ADV5	89603188	830/359	-	940 lm	500 mA	10.9 V	11.8 V	-	-	167 lm/W	> >80
LLE 24x280mm 650lm 835 HV ADV5	28003395	835/359	-	972 lm	500 mA	10.9 V	11.8 V	-	-	170 lm/W	> >80
LLE 24x280mm 650lm 840 HV ADV5	89603189	840/359	-	982 lm	500 mA	10.9 V	11.8 V	-	-	173 lm/W	> >80
LLE 24x280mm 650lm 850 HV ADV5	89603190	850/359	-	988 lm	500 mA	10.9 V	11.8 V	-	-	173 lm/W	> >80
LLE 24x280mm 650lm 865 HV ADV5	89603191	865/359	-	992 lm	500 mA	10.9 V	11.8 V	-	-	173 lm/W	> >80
LLE 24x560mm 1300lm 827 HV ADV5	89603192	827/359	-	1,802 lm	500 mA	21.8 V	23.5 V	-	-	158 lm/W	> >80
LLE 24x560mm 1300lm 830 HV ADV5	89603193	830/359	-	1,875 lm	500 mA	21.8 V	23.5 V	-	-	165 lm/W	> >80
LLE 24x560mm 1300lm 835 HV ADV5	28003397	835/359	-	1,936 lm	500 mA	21.8 V	23.5 V	-	-	169 lm/W	> >80
LLE 24x560mm 1300lm 840 HV ADV5	89603194	840/359	-	1,961 lm	500 mA	21.8 V	23.5 V	-	-	172 lm/W	> >80
LLE 24x560mm 1300lm 850 HV ADV5	89603195	850/359	-	1,976 lm	500 mA	21.8 V	23.5 V	-	-	173 lm/W	> >80
LLE 24x560mm 1300lm 865 HV ADV5	89603196	865/359	-	1,958 lm	500 mA	21.8 V	23.5 V	-	-	173 lm/W	> >80
LLE 24x560mm 1300lm 840 HV ADV5 BT	28002944	840/359	-	1,961 lm	500 mA	21.8 V	23.5 V	-	-	170 lm/W	> >80
LLE 24x560mm 1300lm 865 HV ADV5 BT	28002945	865/359	-	1,958 lm	500 mA	21.8 V	23.5 V	-	-	172 lm/W	> >80

② If mounted with M4 screws and plastic washers.

③ Tolerance of useful light flux - 0 % / + 15 %. Measurement uncertainty $\pm 10\%$.


④ Tolerance of expected light flux - 0 % / + 15 %. Measurement uncertainty $\pm 10\%$. Based on calculation.

⑤ Measurement tolerance forward voltage: $\pm 0.1\text{ V}$.

⑥ Tolerance of power consumption $P_{on} \pm 10\%$. Measurement uncertainty $\pm 5\%$.

LINEAR COVER LLE

Accessory



Product description

- _ LINEAR COVER for LLE
- _ Protection against direct touch for non-SELV applications (recommendation LLE 20: use all fixing points and screwed Endcap, recommendation LLE 24: use all fixing points)
- _ Fast snap on mounting on to LLE 20: with M4 screws and plastic washers, to LLE 24: with clips or plastic washers
- _ High transmission: transparent, semi-transparent and diffuse
- _ Material: PMMA
- _ Tolerances: ± 1 mm for 597 mm length (ends finished), + 10 mm from length 1,150 mm (ends raw)

Website

<http://www.tridonic.com/28000338>



Ordering data

Type	Article number	Colour	Length L	Efficiency	Packaging, carton	Weight per pc.
LINEAR COVER SY Transparent 1600mm	28000338	Transparent	1,600 mm	94 %	12 pc(s).	0.272 kg
LINEAR COVER SY Frosted 1800mm	28000437	Semi-transparent	1,800 mm	87 %	12 pc(s).	0.308 kg
LINEAR COVER SY Frosted 1600mm	28000339	Semi-transparent	1,600 mm	87 %	12 pc(s).	0.272 kg
LINEAR COVER SY Frosted 1500mm	28000435	Semi-transparent	1,500 mm	87 %	12 pc(s).	0.244 kg
LINEAR COVER SY Frosted 1200mm	28000422	Semi-transparent	1,200 mm	87 %	12 pc(s).	0.205 kg
LINEAR COVER SY Frosted 597mm	28000340	Semi-transparent	597 mm	87 %	12 pc(s).	0.102 kg
LINEAR COVER SY Diffuse 1800mm	28000438	Diffuse	1,800 mm	76 %	12 pc(s).	0.308 kg
LINEAR COVER SY Diffuse 1600mm	28000341	Diffuse	1,600 mm	76 %	12 pc(s).	0.272 kg
LINEAR COVER SY Diffuse 1500mm	28000436	Diffuse	1,500 mm	76 %	12 pc(s).	0.257 kg
LINEAR COVER SY Diffuse 1200mm	28000434	Diffuse	1,200 mm	76 %	12 pc(s).	0.205 kg
LINEAR COVER SY Diffuse 597mm	28000342	Diffuse	597 mm	76 %	12 pc(s).	0.102 kg

ACL ENDCAP LLE


Accessory

**Product description**

- _ ENDCAP for LLE
- _ PUSH-FIX: Fast snap on mounting (sheet thickness 0.5 – 1.0 mm), for drilling hole 4 mm
- _ SCREW-FIX: Screw mounting with EJOT Delta PT WN 5451 30x8 (not included), tightening torque 0.7 Nm
- _ Clip made of polycarbonate

Website


<http://www.tridonic.com/28001037>

**Ordering data**

Type	Article number	Colour	Packaging, carton	Weight per pc.
ACL ENDCAP LLE24 PUSH-FIX	28001037	White	480 pc(s).	0.003 kg
ACL ENDCAP LLE24 SCREW-FIX	28002315	White	480 pc(s).	0.003 kg

ACL LINEAR LENS 24mm

Accessory

**Product description LINEAR LENS**

- _ Linear lens for LLE 20 / 24
- _ Available with different beam characteristics
- _ Protection against direct touch for non-SELV applications (recommendation: use all fixing points)
- _ Fast snap on mounting on to LLE 20: with M4 screws and plastic washers, to LLE 24: with clips or plastic washers
- _ Recommendation: Fastening with screws and plastic washers, see 2.3 Heat sink specifications in data sheet
- _ Material: PMMA
- _ Available lengths: 1,200, 1,500 and 1,800 mm, Tolerance: + 10 mm (ends raw)
- _ Max. permissible temperature 80 °C
- _ Photometric data available on website

Product description Endcap

- _ ENDCAP for LINEAR LENS 24mm INTENSE, ASY and DASY
- _ Mounting by clipping in and screwing from below using screw EJOT Delta PT WN 5451 20x4, tightening torque 0.7 Nm
- _ Made of Polyamide UL94 V0

Website

<http://www.tridonic.com/28001428>

**Ordering data**

Type	Article number	Length L	Beam characteristic	Efficiency	Packaging, carton	Weight per pc.
ACL LINEAR LENS 24x1200mm 60°	28001428	1,200 mm	60°	97 %	21 pc(s).	0.196 kg
ACL LINEAR LENS 24x1200mm 90°	28001429	1,200 mm	90°	97 %	21 pc(s).	0.165 kg
ACL LINEAR LENS 24x1500mm 60°	28000953	1,500 mm	60°	97 %	21 pc(s).	0.261 kg
ACL LINEAR LENS 24x1500mm 90°	28000955	1,500 mm	90°	97 %	21 pc(s).	0.221 kg
ACL LINEAR LENS 24x1200mm INTENSE	28002024	1,200 mm	40°	95 %	18 pc(s).	0.261 kg
ACL LINEAR LENS 24x1500mm INTENSE	28002025	1,500 mm	40°	95 %	18 pc(s).	0.326 kg
ACL LINEAR LENS 24x1800mm INTENSE	28002026	1,800 mm	40°	95 %	18 pc(s).	0.392 kg
ACL LINEAR LENS 24x1200mm BATWING	28002027	1,200 mm	batwing	95 %	18 pc(s).	0.275 kg
ACL LINEAR LENS 24x1500mm BATWING	28002028	1,500 mm	batwing	95 %	18 pc(s).	0.344 kg
ACL LINEAR LENS 24x1800mm BATWING	28002029	1,800 mm	batwing	95 %	18 pc(s).	0.412 kg
ACL LINEAR LENS 24x1200mm ASY	28002030	1,200 mm	asymmetric	95 %	18 pc(s).	0.250 kg
ACL LINEAR LENS 24x1500mm ASY	28002031	1,500 mm	asymmetric	95 %	18 pc(s).	0.312 kg
ACL LINEAR LENS 24x1800mm ASY	28002032	1,800 mm	asymmetric	95 %	18 pc(s).	0.375 kg
ACL LINEAR LENS 24x1200mm DASY	28002033	1,200 mm	double asymmetric	92 %	18 pc(s).	0.249 kg
ACL LINEAR LENS 24x1500mm DASY	28002034	1,500 mm	double asymmetric	92 %	18 pc(s).	0.311 kg
ACL LINEAR LENS 24x1800mm DASY	28002035	1,800 mm	double asymmetric	92 %	18 pc(s).	0.373 kg
ACL Endcap LENS 24mm PSF	28002669	-	-	-	3,600 pc(s).	0.003 kg

ACL CLIP 4.3mm


Accessory

**Product description**

- _ Clip for fixation of LED modules with 4.3 mm holes
- _ Fast snap on mounting (sheet thickness 0.5 – 1.0 mm for PUSH-FIX and 1 – 2 mm for PUSH-FIX Long)
- _ For drilling hole 4 mm
- _ Clip made of polycarbonate
- _ Minimum sales quantity 500 pcs.

Website

<http://www.tridonic.com/28001036>


**Ordering data**

Type	Article number	Colour	Packaging, bag ^①	Weight per pc.
ACL CLIP 4.3mm PUSH-FIX	28001036	White	500 pc(s).	0.001 kg
ACL CLIP 4,3mm PUSH-FIX Long	28002314	Transparent	500 pc(s).	0.001 kg

① Minimum sales quantity 500 pcs.

ACL BRIDGE LLE24/40

Accessory

**Product description**

- _ Enables the fixation of 24 mm wide Tridonic LED modules to fixtures made for 40 mm wide modules
- _ Ideal for extruded aluminium gear trays made for 40 mm modules with pre-alignment knobs
- _ Clip-on for LINEAR COVER and LINEAR LENS ^①
- _ For LLE 24 with 280 mm module minimum 2 bridges required
- _ For LLE 24 with 560 mm module minimum 3 bridges required
- _ Fixation via M3 or M4 countersunk screw, max. tightening torque 0.5 Nm
- _ BRIDGE made of white polycarbonate
- _ Minimum sales quantity 600 pcs.

^① Beam characteristics will change due to the elevated fixation (see photometric files for details).

Website

<http://www.tridonic.com/28001205>

**Ordering data**

Type	Article number	Colour	Packaging, carton	Weight per pc.
ACL BRIDGE LLE24/40 SCREW-FIX	28001205	White	600 pc(s).	0.001 kg

1. Standards

IEC 62031
IEC 62471
IEC 61000-4-2
IEC 62778
IEC 61547
UL 8750 (for CLASS2 circuits and dry locations)

1.1 Photometric code

Key for photometric code, e. g. 830 / 349

1 st digit	2 nd + 3 rd digit	4 th digit	5 th digit	6 th digit	
Code	CRI	Colour temperature in Kelvin x 100	MacAdam initial	MacAdam after 25% of the lifetime (max.6000h)	
7	70 – 79			Luminous flux after 25% of the lifetime (max.6000h)	
8	80 – 89			Code	Luminous flux
9	≥90			7	≥ 70 %
				8	≥ 80 %
				9	≥ 90 %

1.2 Energy classification

Type	Colour temperature	Forward current	Energy classification	Energy consumption
LLE 24x70mm 160lm 830 HV ADV5 QTY4	3,000 K	300 mA	C	1 kWh / 1,000 h
LLE 24x70mm 160lm 840 HV ADV5 QTY4	4,000 K	300 mA	C	1 kWh / 1,000 h
LLE 24x140mm 325lm 827 HV ADV5	2,700 K	300 mA	C	2 kWh / 1,000 h
LLE 24x140mm 325lm 830 HV ADV5	3,000 K	300 mA	C	2 kWh / 1,000 h
LLE 24x140mm 325lm 835 HV ADV5	3,500 K	300 mA	C	2 kWh / 1,000 h
LLE 24x140mm 325lm 840 HV ADV5	4,000 K	300 mA	C	2 kWh / 1,000 h
LLE 24x140mm 325lm 865 HV ADV5	6,500 K	300 mA	C	2 kWh / 1,000 h
LLE 24x280mm 650lm 827 HV ADV5	2,700 K	300 mA	C	4 kWh / 1,000 h
LLE 24x280mm 650lm 830 HV ADV5	3,000 K	300 mA	C	4 kWh / 1,000 h
LLE 24x280mm 650lm 835 HV ADV5	3,500 K	300 mA	C	4 kWh / 1,000 h
LLE 24x280mm 650lm 840 HV ADV5	4,000 K	300 mA	C	4 kWh / 1,000 h
LLE 24x280mm 650lm 850 HV ADV5	5,000 K	300 mA	C	4 kWh / 1,000 h
LLE 24x280mm 650lm 865 HV ADV5	6,500 K	300 mA	C	4 kWh / 1,000 h
LLE 24x560mm 1300lm 827 HV ADV5	2,700 K	300 mA	D	7 kWh / 1,000 h
LLE 24x560mm 1300lm 830 HV ADV5	3,000 K	300 mA	C	7 kWh / 1,000 h
LLE 24x560mm 1300lm 835 HV ADV5	3,500 K	300 mA	C	7 kWh / 1,000 h
LLE 24x560mm 1300lm 840 HV ADV5	4,000 K	300 mA	C	7 kWh / 1,000 h
LLE 24x560mm 1300lm 850 HV ADV5	5,000 K	300 mA	C	7 kWh / 1,000 h
LLE 24x560mm 1300lm 865 HV ADV5	6,500 K	300 mA	C	7 kWh / 1,000 h
Backside terminals				
LLE 24x560mm 1300lm 840 HV ADV5 BT	4,000 K	300 mA	C	7 kWh / 1,000 h
LLE 24x560mm 1300lm 865 HV ADV5 BT	6,500 K	300 mA	C	7 kWh / 1,000 h

Energy label and further information at www.tridonic.com in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

2. Thermal details

2.1 tc point, ambient temperature and lifetime

The temperature at tp reference point is crucial for the light output and lifetime of a LED product.

For LLE a tp temperature of 50 °C has to be complied in order to achieve an optimum between heat sink requirements, light output and lifetime.

Compliance with the maximum permissible reference temperature at the tc point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

2.2 Storage and humidity

Storage temperature	-40...+80 °C
---------------------	--------------

Operation only in non condensing environment.

Humidity during processing of the module should be between 30 to 70 %.

2.3 Heat sink values

LLE 24x70mm 160lm ADV5

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	300 mA		self cooling
25 °C	50 °C	500 mA	34.38 K/W	19 cm ²
35 °C	50 °C	300 mA	38.11 K/W	17 cm ²
35 °C	50 °C	500 mA	20.62 K/W	32 cm ²
40 °C	50 °C	300 mA	25.40 K/W	26 cm ²
40 °C	50 °C	500 mA	13.73 K/W	49 cm ²
45 °C	50 °C	300 mA	12.69 K/W	53 cm ²
45 °C	50 °C	500 mA	6.85 K/W	97 cm ²

LLE 24x140mm 325lm ADV5

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	300 mA		self cooling
25 °C	50 °C	500 mA	17.23 K/W	39 cm ²
35 °C	50 °C	300 mA	19.05 K/W	35 cm ²
35 °C	50 °C	500 mA	10.33 K/W	65 cm ²
40 °C	50 °C	300 mA	12.70 K/W	52 cm ²
40 °C	50 °C	500 mA	6.88 K/W	97 cm ²
45 °C	50 °C	300 mA	6.34 K/W	105 cm ²
45 °C	50 °C	500 mA	3.43 K/W	194 cm ²

LLE 24x280mm 650lm ADV5

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	50 °C	300 mA		self cooling
25 °C	50 °C	500 mA	8.61 K/W	77 cm ²
35 °C	50 °C	300 mA	9.50 K/W	70 cm ²
35 °C	50 °C	500 mA	5.17 K/W	129 cm ²
40 °C	50 °C	300 mA	6.33 K/W	105 cm ²
40 °C	50 °C	500 mA	3.44 K/W	194 cm ²
45 °C	50 °C	300 mA	3.16 K/W	211 cm ²
45 °C	50 °C	500 mA	1.72 K/W	388 cm ²

LLE 24x560mm 1300lm ADV5

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25°C	50°C	300 mA		self cooling
25°C	50°C	500 mA	4.31 K/W	155 cm ²
35°C	50°C	300 mA	4.75 K/W	140 cm ²
35°C	50°C	500 mA	2.58 K/W	258 cm ²
40°C	50°C	300 mA	3.16 K/W	211 cm ²
40°C	50°C	500 mA	1.72 K/W	387 cm ²
45°C	50°C	300 mA	1.58 K/W	422 cm ²
45°C	50°C	500 mA	0.86 K/W	776 cm ²

Notes

The actual cooling surface can differ because of the material, the structural shape, outside influences and the installation situation. Depending on the heat sink a heat conducting paste or heat conducting film might be necessary to keep the specified tp temperature.

3. Installation / wiring**3.1 Electrical supply/choice of LED driver**

LLE modules from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED driver which complies with the relevant standards. The use of LED driver from Tridonic in combination with LLE modules guarantees the necessary protection for safe and reliable operation.

If a LED driver other than Tridonic is used, it must provide the following protection:

- Short-circuit protection
- Overload protection
- Overtemperature protection



LLE modules must be supplied by a constant current LED driver. Operation with a constant voltage LED driver will lead to an irreversible damage of the module.

Wrong polarity can damage the LLE.

The LLE module is designed for serial wiring.

With parallel wiring tolerance-related differences in output are possible (thermal stress of the module) and can cause differences in brightness.

If a wire breaks or a complete module fails then the current passing through the other module increases. This may reduce its life considerably.





Max. 8 pieces 280 mm modules or 4 pieces 560 mm modules may be connected in parallel.

LLE can be operated either from SELV LED drivers or from LED drivers with LV output voltage.




LLE are basic insulated up to 440 V (if mounted with M4 screws with head diameter 7 mm in combination with plastic washers) against ground and can be mounted directly on earthed metal parts of the luminaire. If the max. output voltage of the LED driver (also against earth) is above 440 V, an additional insulation between LED module and heat sink is required (for example by insulated thermal pads) or by a suitable luminaire construction.

At voltages > 60 V an additional protection against direct touch (test finger) to the light emitting side of the module has to be guaranteed. This is typically achieved by means of a non removable light distributor over the module.

3.2 Wiring**Wiring examples for serial wiring****Wiring examples for parallel wiring****3.3 Wiring type and cross section**

For wiring use stranded wire with ferrules or solid wire from 0.2 to 0.75 mm². For the push-wire connection you have to strip the insulation (8–9 mm).



To remove the wires use a suitabel tool (e.g. Microcon release pin) or through twist and pull.

3.4 Mounting instruction




None of the components of the LLE (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.

Max. torque for fixing: 0.5 Nm.


The LED modules are mounted onto a heat sink with min. 3 screws per module or ACL CLIP 4.3mm.

The LLE 24x70mm module is delivered as a board of 280mm (4 pcs.) and must be separated.

Only touch the module at the edge to separate the modules (see marking below).



Cut out on gear tray for backside terminal:



Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.

Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.

Avoid corrosive atmosphere during usage and storage.

3.5 EOS/ESD safety guidelines



The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice. Please note the requirements set out in the document EOS / ESD guidelines (Guideline_EOS_ESD.pdf) at: <http://www.tridonic.com/esd-protection>

4. Lifetime

4.1 Lifetime, lumen maintenance and failure rate

The light output of an LED module decreases over the lifetime, this is characterized with the L value.

L70 means that the LED module will give 70 % of its initial luminous flux.

This value is always related to the number of operation hours and therefore defines the lifetime of an LED module.

As the L value is a statistical value and the lumen maintenance may vary over the delivered LED modules.

The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value.

In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

4.2 Lumen maintenance for LLE 24mm HV ADV5

Forward current	tp temperature	tp						
		L90 / F10	L90 / F50	L80 / F10	L80 / F50	L70 / F10	L70 / F50	
150 mA	40 °C	43,000 h	59,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	45 °C	42,000 h	57,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	50 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	55 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	60 °C	39,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	65 °C	38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	70 °C	38,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	75 °C	37,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	80 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	85 °C	35,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	200 mA	40 °C	43,000 h	58,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		45 °C	42,000 h	57,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		50 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
55 °C		40,000 h	53,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
60 °C		39,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
65 °C		38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
70 °C		37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
75 °C		36,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
80 °C		36,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
85 °C		35,000 h	44,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
300 mA		40 °C	42,000 h	58,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		45 °C	41,000 h	56,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		50 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	40,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	60 °C	39,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	65 °C	38,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	70 °C	37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	75 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	80 °C	35,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	85 °C	34,000 h	44,000 h	70,000 h	>72,000 h	>72,000 h	>72,000 h	

Forward current	tp temperature	tp						
		L90 / F10	L90 / F50	L80 / F10	L80 / F50	L70 / F10	L70 / F50	
375 mA	40 °C	42,000 h	57,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	45 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	50 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	55 °C	39,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	60 °C	38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	65 °C	37,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	70 °C	37,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	75 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	80 °C	35,000 h	44,000 h	71,000 h	>72,000 h	>72,000 h	>72,000 h	
	85 °C	34,000 h	43,000 h	69,000 h	>72,000 h	>72,000 h	>72,000 h	
	450 mA	40 °C	42,000 h	56,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		45 °C	41,000 h	55,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		50 °C	40,000 h	53,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
55 °C		39,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
60 °C		38,000 h	50,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
65 °C		37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
70 °C		36,000 h	47,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
75 °C		35,000 h	45,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
80 °C		35,000 h	44,000 h	70,000 h	>72,000 h	>72,000 h	>72,000 h	
85 °C		34,000 h	43,000 h	69,000 h	>72,000 h	>72,000 h	>72,000 h	
500 mA		40 °C	41,000 h	56,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		45 °C	40,000 h	54,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
		50 °C	39,000 h	52,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h
	55 °C	38,000 h	51,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	60 °C	38,000 h	49,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	65 °C	37,000 h	48,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	70 °C	36,000 h	46,000 h	>72,000 h	>72,000 h	>72,000 h	>72,000 h	
	75 °C	35,000 h	45,000 h	71,000 h	>72,000 h	>72,000 h	>72,000 h	
	80 °C	34,000 h	43,000 h	70,000 h	>72,000 h	>72,000 h	>72,000 h	
	85 °C	34,000 h	42,000 h	68,000 h	>72,000 h	>72,000 h	>72,000 h	

4.3 Switching capability

100,000 cycles

Tridonic test according to IEC 62717 Cl 10.3.3

30 s on / 30 s off at Imax

5. Electrical values

5.1 Declaration of electrical parameters

Irated ... Nominal operating current the module is designed for.


I_{max} ... Max. permissible continuous operating current incl. The tolerances of the LED driver.

Max. permissible LF current ripple ... Max. output current of the LED driver incl. Tolerances and LF current ripple must not exceed this value.


Max. permissible peak current ... The max. output peak current of the LED driver must not exceed this value.

5.2 Typ. forward voltage vs. forward current


LLE 24x70mm 160lm 8xx HV ADV5




LLE 24x140mm 325lm 8xx HV ADV5



LLE 24x280mm 650lm 8xx HV ADV5




LLE 24x560mm 1300lm 8xx HV ADV5



The diagrams are based on statistic values.
The real values can be different.

5.3 Forward voltage vs. tc temperature



The diagrams are based on statistic values.
The real values can be different.



6. Photometric characteristics

6.1 Coordinates and tolerances according to CIE 1931

The specified colour coordinates are integral measured by current impulse of 195 mA and a duration of 100 ms.
 The ambient temperature of the measurement is $t_a = 25^\circ\text{C}$.
 The measurement tolerance of the colour coordinates are ± 0.01 .



2,700 K

	x0	y0
Centre	0.4578	0.4101





3,000 K

	x0	y0
Centre	0.4338	0.4030




3,500 K

	x0	y0
Centre	0.4073	0.3917




4,000 K

	x0	y0
Center	0.3818	0.3797




— MacAdam Ellipse: 3SDCM




5,000 K

	x0	y0
Center	0.3447	0.3553




— MacAdam Ellipse: 3SDCM




6,500 K

	x0	y0
Center	0.3123	0.3282




— MacAdam Ellipse: 3SDCM




6.2 Light distribution

The optical design of the LLE product line ensures optimum homogeneity for the light distribution.




The colour temperature is measured integral over the complete module. The single LED light points can have deviations in the colour coordinates within MacAdam 5. To ensure an ideal mixture of colours and a homogeneous light distribution a suitable optic (e. g. PMMA diffuser) and a sufficient spacing between module and optic (typ. 4 cm) should be used.

6.3 Relative luminous flux vs. tc temperature



6.4 Relative luminous flux vs. operating current



The diagrams are based on statistic values. The real values can be different.

7. Miscellaneous

7.1 Additional information

Additional technical information at www.tridonic.com → Technical Data

Guarantee conditions at www.tridonic.com → Services

Lifetime declarations are informative and represent no warranty claim.