

Module LLE 24mm 750lm LV DAISY ADV1 (LEDiL)

Modules LLE advanced



LLE 24x280mm 750lm LVD ADV1



Module with LEDiL DAISY lens system



For articles manufactured at Tridonic SRB d.o.o.

Product description

- _ Ideal for linear luminaires
- _ 4 terminals for parallel wiring
- _ SELV module – the single module has a forward voltage < 60 V
- _ Push terminals for quick and simple wiring of LED module to LED module
- _ Design for LEDiL DAISY 7x1 / 28x1 and LEDiL BRIANNA 7x1 / 14x1 / 28x1 portfolio
- _ HE ... High Efficiency, NM ... Nominal Mode, HO ... High Output
- _ Orders only in full carton quantities.
- _ Long lifetime up to 72,000 hours
- _ 5 years guarantee (conditions at <https://www.tridonic.com/en/int/services/manufacturer-guarantee-conditions>)

Optical properties


- _ Colour temperatures 3,000 and 4,000 K
- _ Useful luminous flux 1,512 lm at Irated and tp = 25 °C
- _ Efficacy of the LED module 202 lm/W at Irated and tp = 25 °C
- _ High colour rendering index CRI > 80
- _ High colour consistency (MacAdam 3) ^①
- _ Small luminous flux tolerances

Mechanical properties

- _ Module dimension 24 x 280 mm and 24 x 560 mm
- _ Simple installation of lens and module with M3 screws

System solution

- _ Integrate compatible partner products into your final system solution:
<https://www.tridonic.com/en/int/products/accessories#partner>
- _ Combine Tridonic's LED modules and dimmable drivers to achieve an outstanding system efficacy (configuration possible via <https://setbuilder.tridonic.com/>)

^① Integral measurement over the complete module.**Website**<http://www.tridonic.com/89603462>

Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street




Decorative




High bay

Module LLE 24mm 750lm LV DAISY ADV1 (LEDiL)

Modules LLE advanced



LLE 24x280mm 750lm LVD ADV1



LLE 24x560mm 1500lm LVD ADV1

Ordering data

Type	Article number	Colour temperature	Packaging, carton	Weight per pc.
LLE 24x280mm 750lm 830 LVD ADV1	89603462	3,000 K	108 pc(s).	0.023 kg
LLE 24x280mm 750lm 840 LVD ADV1	89603463	4,000 K	108 pc(s).	0.023 kg
LLE 24x560mm 1500lm 830 LVD ADV1	89603464	3,000 K	108 pc(s).	0.046 kg
LLE 24x560mm 1500lm 840 LVD ADV1	89603465	4,000 K	108 pc(s).	0.046 kg

Technical data

Beam characteristic	120°
Ambient temperature t_a	-40 ... +65 °C
t_p rated	65 °C
t_c	80 °C
I _{rated} for 750 lm	100 mA
I _{rated} for 1,500 lm	200 mA
I _{max} for 750 lm	350 mA
I _{max} for 1,500 lm	700 mA
Max. permissible LF current ripple for 750 lm	440 mA
Max. permissible LF current ripple for 1,500 lm	880 mA
Max. permissible peak current for 750 lm	600 mA / max. 10 ms
Max. permissible peak current for 1,500 lm	1,200 mA / max. 10 ms
Max. working voltage for insulation SELV ^②	< 60 V
Insulation test voltage	0.5 kV
CTI of the printed circuit board	≥ 600
Colour tolerance	3 SDCM
ESD classification	Severity level 4
Risk group (IEC 62471) ^③	RG1
Classification acc. to IEC 62031	Built-in
Type of protection	IP00
Lumen maintenance L70B50	72,000 h
Guarantee (conditions at www.tridonic.com)	5 Year(s)

Approval marks**Standards**

IEC 62031, IEC 62471, IEC 61000-4-2, IEC 62778, IEC 61547, UL 8750

Specific technical data

Type	Article number	Photometric code	Useful luminous flux at $t_p = 25\text{ °C}$ ^④	Expected luminous flux at t_p rated ^⑤	Typ. forward current	Min. forward voltage at t_p rated	Max. forward voltage at $t_p = 25\text{ °C}$	Power consumption P_{on} at $t_p = 25\text{ °C}$ ^⑥	Efficacy of the module at $t_p = 25\text{ °C}$	Expected efficacy of the module at t_p rated	Colour rendering index CRI
LLE 24x280mm 750lm – Operating mode NM at 100 mA											
LLE 24x280mm 750lm 830 LVD ADV1	89603462	830/359	723 lm	693 lm	100 mA	35.6 V	38.8 V	3.8 W	190 lm/W	187 lm/W	>80
LLE 24x280mm 750lm 840 LVD ADV1	89603463	840/359	761 lm	721 lm	100 mA	35.6 V	38.8 V	3.8 W	200 lm/W	194 lm/W	>80
LLE 24x280mm 750lm – Operating mode HO at 200 mA											
LLE 24x280mm 750lm 830 LVD ADV1	89603462	830/359	–	1,327 lm	200 mA	36.7 V	40.0 V	–	–	172 lm/W	>80
LLE 24x280mm 750lm 840 LVD ADV1	89603463	840/359	–	1,384 lm	200 mA	36.7 V	40.0 V	–	–	180 lm/W	>80
LLE 24x280mm 750lm – Operating mode HO at 300 mA											
LLE 24x280mm 750lm 830 LVD ADV1	89603462	830/359	–	1,961 lm	300 mA	37.7 V	40.9 V	–	–	166 lm/W	>80
LLE 24x280mm 750lm 840 LVD ADV1	89603463	840/359	–	2,046 lm	300 mA	37.7 V	40.9 V	–	–	173 lm/W	>80
LLE 24x560mm 1500lm – Operating mode NM at 200 mA											
LLE 24x560mm 1500lm 830 LVD ADV1	89603464	830/359	1,451 lm	1,382 lm	200 mA	35.6 V	38.8 V	7.5 W	193 lm/W	185 lm/W	>80
LLE 24x560mm 1500lm 840 LVD ADV1	89603465	840/359	1,512 lm	1,453 lm	200 mA	35.6 V	38.8 V	7.5 W	202 lm/W	194 lm/W	>80
LLE 24x560mm 1500lm – Operating mode HO at 400 mA											
LLE 24x560mm 1500lm 830 LVD ADV1	89603464	830/359	–	2,635 lm	400 mA	36.7 V	40.0 V	–	–	171 lm/W	>80
LLE 24x560mm 1500lm 840 LVD ADV1	89603465	840/359	–	2,767 lm	400 mA	36.7 V	40.0 V	–	–	180 lm/W	>80
LLE 24x560mm 1500lm – Operating mode HO at 600 mA											
LLE 24x560mm 1500lm 830 LVD ADV1	89603464	830/359	–	3,899 lm	600 mA	37.7 V	40.9 V	–	–	165 lm/W	>80
LLE 24x560mm 1500lm 840 LVD ADV1	89603465	840/359	–	4,091 lm	600 mA	37.7 V	40.9 V	–	–	173 lm/W	>80

② If mounted with M3 screws in combination with LEDIL DAISY lens.

③ Measured at operating mode HO.

④ Tolerance of useful light flux - 0 % / + 15 %. Measurement uncertainty ± 10 %.

⑤ Tolerance of expected light flux - 0 % / + 15 %. Measurement uncertainty ± 10 %. Based on calculation.

⑥ Tolerance of power consumption P_{on} ± 10 %. Measurement uncertainty ± 5 %.

1. Standards

IEC 62031
 IEC 62471
 IEC 61000-4-2
 IEC 62778
 IEC 61547
 UL 8750 (for CLASS2 circuits and dry locations)

1.1 Photometric code

Key for photometric code, e. g. 830 / 349

1 st digit	2 nd + 3 rd digit	4 th digit	5 th digit	6 th digit
Code	CRI	Colour temperature in Kelvin x 100	MacAdam after 25% of the lifetime (max.6000h)	Luminous flux after 25% of the lifetime (max.6000h)
7	70 – 79	MacAdam initial	(max.6000h)	Code
8	80 – 89			Luminous flux
9	≥90			

1.2 Energy classification

Type	Colour temperature	Forward current	Energy classification	Energy consumption
LLE 24x280mm 750lm 830 LVD ADV1	3,000 K	100 mA	C	4 kWh / 1,000 h
LLE 24x280mm 750lm 840 LVD ADV1	4,000 K	100 mA	B	4 kWh / 1,000 h
LLE 24x560mm 1500lm 830 LVD ADV1	3,000 K	200 mA	C	8 kWh / 1,000 h
LLE 24x560mm 1500lm 840 LVD ADV1	4,000 K	200 mA	B	8 kWh / 1,000 h

Energy label and further information at www.tridonic.com in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

2. Thermal details

2.1 tc point, ambient temperature and lifetime

The temperature at tp reference point is crucial for the light output and lifetime of a LED product.

For LLE a tp temperature of 65 °C has to be complied in order to achieve an optimum between heat sink requirements, light output and lifetime.

Compliance with the maximum permissible reference temperature at the tc point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

2.2 Storage and humidity

Storage temperature	-40 ... +80 °C
---------------------	----------------

Operation only in non condensing environment.

Humidity during processing of the module should be between 30 to 70 %.

2.3 Heat sink values

LLE 24x280mm 750lm LVD ADV1

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	65 °C	100 mA		self cooling
25 °C	65 °C	300 mA	8.1 K/W	82 cm ²
35 °C	65 °C	100 mA		self cooling
35 °C	65 °C	300 mA	6.1 K/W	109 cm ²
40 °C	65 °C	100 mA		self cooling
40 °C	65 °C	300 mA	5.0 K/W	131 cm ²
45 °C	65 °C	100 mA		self cooling
45 °C	65 °C	300 mA	4.0 K/W	164 cm ²
50 °C	65 °C	100 mA	9.7 K/W	69 cm ²
50 °C	65 °C	300 mA	3.0 K/W	219 cm ²

LLE 24x560mm 1500lm LVD ADV1

ta	tp	Forward current	R _{th, hs-a}	Cooling area
25 °C	65 °C	200 mA		self cooling
25 °C	65 °C	600 mA	4.0 K/W	164 cm ²
35 °C	65 °C	200 mA		self cooling
35 °C	65 °C	600 mA	3.0 K/W	219 cm ²
40 °C	65 °C	200 mA		self cooling
40 °C	65 °C	600 mA	2.5 K/W	263 cm ²
45 °C	65 °C	200 mA		self cooling
45 °C	65 °C	600 mA	2.0 K/W	329 cm ²
50 °C	65 °C	200 mA	4.8 K/W	139 cm ²
50 °C	65 °C	600 mA	1.5 K/W	438 cm ²

Notes

The actual cooling surface can differ because of the material, the structural shape, outside influences and the installation situation. Depending on the heat sink a heat conducting paste or heat conducting film might be necessary to keep the specified tp temperature.

3. Installation / wiring

3.1 Electrical supply/choice of LED driver

LLE modules from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED driver which complies with the relevant standards. The use of LED driver from Tridonic in combination with LLE modules guarantees the necessary protection for safe and reliable operation.

If a LED driver other than Tridonic is used, it must provide the following protection:

- Short-circuit protection
- Overload protection
- Overtemperature protection



LLE modules must be supplied by a constant current LED driver. Operation with a constant voltage LED driver will lead to an irreversible damage of the module.

Wrong polarity can damage the LLE.

With parallel wiring tolerance-related differences in output are possible (thermal stress of the module) and can cause differences in brightness.

If a wire breaks or a complete module fails then the current passing through the other module increases. This may reduce its life considerably.

The max. permissible output current of the LED driver for parallel wiring is 3 A.

For parallel wiring only modules of the same forward voltage bin may be used.

The forward voltage bin is indicated on the label of the module.

89603460	LLE 24x140mm 400lm 830 LVD ADV1	3000K
09/2019	12345678 1234 AY34	Tc: 80°C
I _{rated} /max=	100/350mA DC	V _{f,typ} = 21,3/22,7V
		CoO: AT




The 24x1120mm module is not designed for parallel wiring. Due to the module design only 280 and 560 mm modules can be combined with each other.

LLE have to be operated with SELV LED drivers.





LLE are basic insulated up to 60 V SELV (if mounted with M3 screws in combination with LEDiL DAISY lens) against ground and can be mounted directly on earthed metal parts of the luminaire. If the max. output voltage of the LED driver (also against earth) is above 60 V SELV, an additional insulation between LED module and heat sink is required (for example by insulated thermal pads) or by a suitable luminaire construction.

3.2 Wiring



Wiring examples




Type	Max. number with parallel wiring*
LLE 24x280mm 750lm LVD ADV1	6
LLE 24x560mm 1500lm LVD ADV1	3


* with direkt chaining (without additional terminals).

3.3 Wiring type and cross section


For horizontal wiring use stranded wire of 0.5 mm² or solid wire from 0.2 to 0.5 mm² (stripping length 8 - 9 mm) and for vertical wiring solid wire with 0.5 mm² (stripping length > 3 mm). Only one wire per terminal allowed.



wire preparation (horizontal):
0.2 - 0.5 mm²





wire preparation (vertical):
0.5 mm²



Removing the wires through twist and pull.

Cut-out for vertical wiring:



3.4 Mounting instruction



None of the components of the LLE (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.

Max. torque for fixing: 0.5 Nm.

The LED modules are mounted onto a heat sink with min. 2 screws per module.

Only touch the module at the edge to separate the modules (see marking below).



Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.

Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.

Avoid corrosive atmosphere during usage and storage.

3.5 EOS/ESD safety guidelines



The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice. Please note the requirements set out in the document EOS / ESD guidelines (Guideline_EOS_ESD.pdf) at: <http://www.tridonic.com/esd-protection>

4. Lifetime

4.1 Lifetime, lumen maintenance and failure rate

The light output of an LED module decreases over the lifetime, this is characterized with the L value.

L70 means that the LED module will give 70 % of its initial luminous flux.

This value is always related to the number of operation hours and therefore defines the lifetime of an LED module.

As the L value is a statistical value and the lumen maintenance may vary over the delivered LED modules.

The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value.

In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

4.2 Lumen maintenance for LLE 24mm LVD ADV1

LLE 24x280mm LVD ADV1

Forward current	tp tempera- ture	L90 / F10	L90 / F50	L80 / F10	L80 / F50	L70 / F10	L70 / F50
100 mA	40 °C	43,000 h	59,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	45 °C	42,000 h	57,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	50 °C	41,000 h	55,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	55 °C	40,000 h	54,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	60 °C	39,000 h	52,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	65 °C	38,000 h	50,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	70 °C	38,000 h	49,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	75 °C	37,000 h	47,000 h	74,000 h	>75,000 h	>75,000 h	>75,000 h
	80 °C	36,000 h	46,000 h	73,000 h	>75,000 h	>75,000 h	>75,000 h

LLE 24x560mm LVD ADV1

Forward current	tp tempera- ture	L90 / F10	L90 / F50	L80 / F10	L80 / F50	L70 / F10	L70 / F50
200 mA	40 °C	43,000 h	59,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	45 °C	42,000 h	57,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	50 °C	41,000 h	55,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	55 °C	40,000 h	54,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	60 °C	39,000 h	52,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	65 °C	38,000 h	50,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	70 °C	38,000 h	49,000 h	>75,000 h	>75,000 h	>75,000 h	>75,000 h
	75 °C	37,000 h	47,000 h	74,000 h	>75,000 h	>75,000 h	>75,000 h
	80 °C	36,000 h	46,000 h	73,000 h	>75,000 h	>75,000 h	>75,000 h

4.3 Switching capability

100,000 cycles

Tridonic test according to IEC 62717 Cl 10.3.3

30 s on / 30 s off at Imax

5. Electrical values

5.1 Declaration of electrical parameters

I_{rated} ... Nominal operating current the module is designed for.


I_{max} ... Max. permissible continuous operating current incl. The tolerances of the LED driver.

Max. permissible LF current ripple ... Max. output current of the LED driver incl. Tolerances and LF current ripple must not exceed this value.


Max. permissible peak current ... The max. output peak current of the LED driver must not exceed this value.

5.2 Typ. forward voltage vs. forward current

LLE 24x280mm 750lm 8xx LVD ADV1




LLE 24x560mm 1500lm 8xx LVD ADV1



The diagrams are based on statistic values.
The real values can be different.

5.3 Forward voltage vs. t_c temperature



The diagrams are based on statistic values.
The real values can be different.

6. Photometric characteristics

6.1 Coordinates and tolerances according to CIE 1931

The specified colour coordinates are measured integral after a settling time of 100 ms. The current impuls depends on the module type.



The ambient temperature of the measurement is $t_a = 25^\circ\text{C}$.

The measurement tolerance of the colour coordinates are ± 0.01 .

Module type	Current impulse
LLE 24x280mm 750lm xxx LVD ADV1	130 mA
LLE 24x560mm 1500lm xxx LVD ADV1	260 mA



3,000 K

	x0	y0
Centre	0.4338	0.4030




4,000 K

	x0	y0
Center	0.3818	0.3797



6.2 Light distribution


The optical design of the LLE product line ensures optimum homogeneity for the light distribution.



The colour temperature is measured integral over the complete module. The single LED light points can have deviations in the colour coordinates within MacAdam 5.


To ensure an ideal mixture of colours and a homogeneous light distribution a suitable optic (e. g. PMMA diffuser) and a sufficient spacing between module and optic (typ. 4 cm) should be used.

6.3 Relative luminous flux vs. tc temperature




6.4 Relative luminous flux vs. operating current

LLE 24x280mm LVD ADV1



LLE 24x560mm LVD ADV1



The diagrams are based on statistic values.
The real values can be different.

7. Miscellaneous

7.1 Additional information

Additional technical information at www.tridonic.com → Technical Data

Guarantee conditions at www.tridonic.com → Services

Lifetime declarations are informative and represent no warranty claim.