









2. Operating basicDIM ILD with other sensors

2.1. Basic functions




Ikön	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	ON	✓	✓	✓
	OFF	✓	✓	✓
	Dim up	✓	✓	✓
	Dim down	✓	✓	✓
	Automatic mode	✓	✓	✓
	Set current light level	✓	✓	✓

2.2. Push to make switch functions






The abbreviation PTM stands for “push to make switch”.

Ikon	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	PTM Set ON		✓	
	PTM Set OFF		✓	



2.3. Constant light control settings

Ikon	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	Light level low		✓	
	Light level middle		✓	
	Light level high		✓	









2.4. Offset settings







Ikon	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	Offset Value 0 %			
	Offset Value -30 %			
	Offset Value -50 %			
	Offset Mode Converging			
	Offset Mode Fixed			

2.5. Bright Out settings



Ikon	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	Bright Out ON		<input checked="" type="checkbox"/>	
	Bright Out OFF		<input checked="" type="checkbox"/>	

2.6. Presence detection profile settings



Ikon	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	P.I.R. inactive		✓	
	P.I.R. off only		✓	
	P.I.R. active		✓	
	Time delay 1min.		✓	
	Time delay 10min.		✓	
	Time delay 20min.		✓	
	If vacant 0min.		✓	
	If vacant 1min.		✓	

	If vacant 30min.		<input checked="" type="checkbox"/>	
	If vacant continuous		<input checked="" type="checkbox"/>	
	Sec. Level 1%		<input checked="" type="checkbox"/>	
	Sec. Level 10%		<input checked="" type="checkbox"/>	
	Sec. Level 30%		<input checked="" type="checkbox"/>	
	Sec. Level 50%		<input checked="" type="checkbox"/>	

2.7. Interface operating mode settings

Ikon	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	DALI		<input checked="" type="checkbox"/>	
	DSI		<input checked="" type="checkbox"/>	

2.8. Return of power settings

Ikon	Beteckning	DALI MSensor 02	DSI-SMART PTM	SMART Sensor 5-10DPI 19fe
	Power Up ON		✓	
	Power Up OFF		✓	